

amp lid board specks 18-19

	UNW8 156	UNW8 159	UNW8 163		Paradigma 156	Paradigma 159	Paradigma 163		Creamer, Creamer Split, Milligram 158	Creamer, Creamer Split, Milligram 163	Creamer, Creamer Split, Milligram 165	Creamer, Creamer Split, Milligram 168
in (mm)				in (mm)				in (mm)				
overall length	1560	1590	1630	overall length	1560	1590	1630	overall length	1580	1630	1650	1680
nose length	220	220	220	nose length	220	220	220	nose length	250	250	250	250
running length	1140	1170	1210	running length	1130	1160	1200	running length	1140	1190	1210	1240
tail length	200	200	200	tail length	210	210	210	tail length	190	190	190	190
waist width	254	258	262	waist width	254	258	262	waist width	255	255	255	255
nose width	287	302	307	nose width	287	302	307	nose width	299	303	310	313
tail width	295	300	305	tail width	297	302	307	tail width	293	297	304	307
taper	2	2	2	taper	0	0	0	taper	6	6	6	6
sidecut depth	21.0	21.5	22.0	sidecut depth	21.5	22.0	22.5	sidecut depth	20.5	20.5	21.0	21.0
sidecut radius	7.75	8.00	8.35	sidecut radius	7.45	7.70	8.05	sidecut radius	8.25	8.60	8.90	9.10
stance position	10 back	10 back	10 back	stance position	centered + powderstance	centered + powderstance	centered + powderstance	stance position	15 back	15 back	15 back	15 back
nose radius	512	512	512	nose radius	500	500	500	nose radius	600	600	600	600
tail radius	500	500	500	tail radius	500	500	500	tail radius	400	400	500	500
ref stance	54 (50-58)	55 (51-59)	57 (53-61)	ref stance	54 (50 - 58+2)	55 (51-59+2)	57 (53-61+2)	ref stance	55 (51-59)	56 (52 - 60)	57 (53-61)	58 (54-62)
camber depth	7	8	9	camber depth	3	4	5	camber depth	6	7	7	8
camber	Pop Camber	Pop Camber	Pop Camber	camber	Twin Cruise Camber	Twin Cruise Camber	Twin Cruise Camber	camber	Dir. Cruise Camber	Dir. Cruise Camber	Dir. Cruise Camber	Dir. Cruise Camber

	Stereo 152	Stereo 155	Stereo 158		Millisurf/Surfari 157	Millisurf/Surfari 161		Pentaquark 158		Dada	Aloha Vibes
in (mm)				in (mm)			in (mm)		in (mm)		
overall length	1520	1550	1580	overall length	1570	1610	overall length	1580	overall length	1540	1540
nose length	225	225	225	nose length	295	295	nose length	220	nose length	289	309
running length	1070	1100	1130	running length	1120	1160	running length	1210	running length	1009	1090
tail length	225	225	225	tail length	155	155	tail length	150	tail length	242	141
waist width	252	257	260	waist width	260	264	waist width	260	waist width	275	280
nose width	294	299	303	nose width	308	313	nose width	306	nose width	312	323
tail width	294	299	303	tail width	292	297	tail width	300	tail width	305	302
taper	0	0	0	taper	16	16	taper	6	taper	7	21
sidecut depth	21.0	21.0	21.5	sidecut depth	20.0	20.5	sidecut depth	21.5	sidecut depth	16.8	16.3
sidecut radius	7.00	7.30	7.50	sidecut radius	8.00	8.40	sidecut radius	8.60	sidecut radius	7.65	9.25
stance position	centered	centered	centered	stance position	10 back	10 back	stance position	10 back	stance position	15 back	18 back
nose radius	600	600	600	nose radius	800	800	nose radius	512	nose radius	860/400	800
tail radius	600	600	600	tail radius	800	800	tail radius	500	tail radius	860/400	800
ref stance	55 (51-59)	56 (52-60)	58 (54-62)	ref stance	56 (52-60)	58 (54-62)	ref stance	57 (53-61)	ref stance	57 (53-61)	56 (52 - 60)
camber depth	4	5	5	camber depth	5	5	camber depth	9	camber depth	3	5
camber	Twin Cruise Camber	Twin Cruise Camber	Twin Cruise Camber	camber	Dir. Cruise Camber	Dir. Cruise Camber	camber	Pop Camber	camber	Twin Cruise Camber	Dir. Cruise Camber

	Lovelife, Life Split 148	Lovelife, Life Split, Milligram 153		Gogo 144	Gogo 148
in (mm)			in (mm)		
overall length	1480	1530	overall length	1440	1480
nose length	235	235	nose length	220	220
running length	1040	1090	running length	1010	1050
tail length	205	205	tail length	210	210
waist width	242	245	waist width	240	244
nose width	283	287	nose width	280	285
tail width	280	284	tail width	280	285
taper	3	3	taper	0	0
sidecut depth	19.8	20.3	sidecut depth	20.0	20.5
sidecut radius	7.05	7.25	sidecut radius	6.50	6.80
stance position	10 back	10 back	stance position	5 back	5 back
nose radius	600	600	nose radius	400	400
tail radius	400	400	tail radius	400	400
ref stance	53 (49 - 57)	54 (50 - 58)	ref stance	53 (49 - 57)	54 (50 - 58)
camber depth	5	5	camber depth	2	2
camber	Dir. Cruise Camber	Dir. Cruise Camber	camber	Hybrid-V	Hybrid-V